



JCT620X-FO Series 20A SCRs


Rev.1.2

DESCRIPTION:

With high ability to withstand the shock loading of large current, JCT620X-FO SCRs provide high dV/dt rate with strong resistance to electromagnetic interference. They are especially recommended for use on solid state relay, motorcycle, power charger, T-tools etc. From all three terminals to external heatsink, JCT620A-FO provides a rated insulation voltage of 2500 V_{RMS} , complying with UL standards (File ref: E252906). All the packages mentioned are RoHS compliant. (2011/65/EU)

MAIN FEATURES

Symbol	JCT620
V_{DRM}/V_{RRM}	600V
$I_{T(RMS)}$	20A
I_{GT}	3~8mA



ABSOLUTE MAXIMUM RATINGS

Parameter		Symbol	Value	Unit
Storage junction temperature range		T_{stg}	-40-150	$^{\circ}C$
Operating junction temperature range		T_j	-40-150	$^{\circ}C$
Repetitive peak off-state voltage($T_j=150^{\circ}C$)		V_{DRM}	600	V
Repetitive peak reverse voltage($T_j=150^{\circ}C$)		V_{RRM}	600	V
RMS on-state current	TO-220A(Ins) ($T_c=100^{\circ}C$)	$I_{T(RMS)}$	20	A
	TO-220C ($T_c=125^{\circ}C$)			
Average on-state current	TO-220A(Ins) ($T_c=100^{\circ}C$)	$I_{T(AV)}$	13	A
	TO-220C ($T_c=125^{\circ}C$)			
Non repetitive surge peak on-state current ($t_p=10ms$)		I_{TSM}	250	A
I^2t value for fusing ($t_p=10ms$)		I^2t	312.5	A^2s

Critical rate of rise of on-state current ($I_G=2 \times I_{GT}$)	di/dt	125	A/ μ s
Peak gate current	I_{GM}	4	A
Average gate power dissipation	$P_{G(AV)}$	1	W
Peak gate power	P_{GM}	5	W

ELECTRICAL CHARACTERISTICS ($T_j=25^\circ\text{C}$ unless otherwise specified)

Symbol	Test Condition	Value			Unit
		MIN.	TYP.	MAX.	
I_{GT}	$V_D=12\text{V}$ $R_L=33\Omega$	3	-	8	mA
V_{GT}		-	-	1.3	V
V_{GD}	$V_D=V_{DRM}$ $T_j=150^\circ\text{C}$ $R_L=3.3\text{k}\Omega$	0.2	-	-	V
I_L	$I_G=1.2I_{GT}$	-	-	70	mA
I_H	$I_T=500\text{mA}$	-	-	60	mA
dv/dt	$V_D=2/3V_{DRM}$ Gate Open $T_j=150^\circ\text{C}$	300	-	-	V/ μ s
t_{on}	$I_G=20\text{mA}$ $I_A=200\text{mA}$ $I_R=20\text{mA}$ $T_j=25^\circ\text{C}$	-	-	4	μ s
t_{off}		-	-	12	μ s

STATIC CHARACTERISTICS

Symbol	Parameter		Value(MAX)	Unit
V_{TM}	$I_{TM}=40\text{A}$ $t_p=380\mu\text{s}$	$T_j=25^\circ\text{C}$	1.5	V
V_{TO}	Threshold voltage	$T_j=150^\circ\text{C}$	0.89	V
R_d	Dynamic resistance	$T_j=150^\circ\text{C}$	13.79	m Ω
I_{DRM}/I_{RRM}	$V_D=V_{DRM}$ $V_R=V_{RRM}$	$T_j=25^\circ\text{C}$	5	μ A
		$T_j=150^\circ\text{C}$	1	mA

THERMAL RESISTANCES

Symbol	Parameter		Value	Unit
$R_{th(j-c)}$	junction to case(AC)	TO-220A(Ins)	2	$^\circ\text{C}/\text{W}$
		TO-220C	1	

ORDERING INFORMATION

J	CT	6	20	A	-FO
JieJie Microelectronics Co., Ltd.	SCRs	$6: V_{DRM} / V_{RRM} \geq 600V$	$I_{T(RMS)}: 20A$	A: TO-220A(Ins) C: TO-220C	Fast off

MARKING










 Diagram of JCT620A marking: The package has a circular hole at the top. Below it, the marking 'JCT620A' is shown with 'FO' to its right. Below the part number, 'XXX' and 'XXX' are separated by a circle. The package has three pins at the bottom.	 Diagram of JCT620C marking: The package has a circular hole at the top. Below it, the marking 'JCT620C' is shown with 'FO' to its right. Below the part number, 'XXX' and 'XXX' are separated by a circle. The package has three pins at the bottom.
 XXX XXX Year Production Month Code	

FIG.1: Maximum power dissipation versus RMS on-state current**FIG.3:** Surge peak on-state current versus number of cycles**FIG.5:** Non-repetitive surge peak on-state current for a sinusoidal pulse with width $t_p < 10\text{ms}$, and corresponding value of I^2t ($di/dt < 125\text{A}/\mu\text{s}$)**FIG.2:** RMS on-state current versus case temperature**FIG.4:** On-state characteristics (maximum values)**FIG.6:** Relative variations of gate trigger current, holding current and latching current versus junction temperature


**ORDERING INFORMATION**

Order code	Voltage $V_{\text{DRM}}/V_{\text{RRM}}$ (V)	IGT(mA)	Package	Base qty. (pcs)	Delivery mode
JCT620A-FO	600	3~8	TO-220A(Ins)	50	Tube
JCT620C-FO			TO-220C		

Document Revision History


Date	Revision	Changes
Jun.21, 2022	1	Last update
Sept.5, 2022	1.1	Add $I_{\text{T(AV)}}$
Oct.10, 2025	1.2	Revise PACKAGE MECHANICAL DATA

PACKAGE MECHANICAL DATA




Ref.	Dimensions					
	Millimeters			Inches		
	Min.	Typ.	Max.	Min.	Typ.	Max.
A	4.40		4.60	0.173		0.181
B	0.61		0.88	0.024		0.035
C	0.46		0.70	0.018		0.028
C2	1.21		1.32	0.048		0.052
C3	2.40		2.72	0.094		0.107
D	8.60		9.70	0.339		0.382
E	9.80		10.40	0.386		0.409
E1	1.00		1.40	0.039		0.055
F	6.25		6.85	0.246		0.270
G	2.40		2.70	0.094		0.106
H	28.00		29.80	1.102		1.173
H1	1.80		2.20	0.071		0.087
I	4.80		5.20	0.189		0.205
J	9.55		9.95	0.376		0.392
K	4.80		5.20	0.189		0.205
L1	3.45		4.05	0.136		0.159
L2	1.14		1.70	0.045		0.067
L3	2.65		2.95	0.104		0.116
V1		45°			45°	

DELIVERY MODE




PACKAGE	OUTLINE	TUBE (PCS)	INNER BOX (PCS)	PER CARTON
TO-220A	TUBE	50	1,000	5,000

PACKAGE MECHANICAL DATA



Ref.	Dimensions					
	Millimeters			Inches		
	Min.	Typ.	Max.	Min.	Typ.	Max.
A	4.40		4.60	0.173		0.181
B	0.70		0.90	0.028		0.035
C	0.45		0.60	0.018		0.024
C2	1.25		1.35	0.049		0.053
C3	2.20		2.60	0.087		0.102
D	8.90		9.90	0.350		0.390
E	9.90		10.30	0.390		0.406
E1	0.80		1.20	0.031		0.047
F	6.30		6.90	0.248		0.272
G	2.40		2.70	0.094		0.106
H	28.00		29.80	1.102		1.173
H1	2.15		2.55	0.085		0.100
I	4.70		5.10	0.185		0.201
K	9.90		10.30	0.390		0.406
L1	2.70		3.30	0.106		0.130
L2	1.14		1.70	0.045		0.067
L3	2.65		2.95	0.104		0.116
M	4.80		5.20	0.189		0.205

DELIVERY MODE



PACKAGE	OUTLINE	TUBE (PCS)	INNER BOX (PCS)	PER CARTON
TO-220C	TUBE	50	1,000	5,000

Information furnished in this document is believed to be accurate and reliable. However, Jiangsu JieJie Microelectronics Co., Ltd. assumes no responsibility for the consequences of use without consideration for such information nor use beyond it. Information mentioned in this document is subject to change without notice, apart from that when an agreement is signed, Jiangsu JieJie complies with the agreement. Products and information provided in this document have no infringement of patents. Jiangsu JieJie assumes no responsibility for any infringement of other rights of third parties which may result from the use of such products and information. This document supersedes and replaces all information previously supplied.

 is a registered trademark of Jiangsu JieJie Microelectronics Co., Ltd.
Copyright © 2025 Jiangsu JieJie Microelectronics Co., Ltd. All rights reserved.