


## JST30F-1200CW 30A TRIAC

Rev.A.1.1

### DESCRIPTION:

The JST30F-1200CW triac is suitable for general purpose AC switching. It can be used as an ON/OFF function in applications such as heating regulation, induction motor starting circuits, for phase control operation in light dimmers, motor speed controllers. JST30F-1200CW snubberless triac is especially recommended for use on inductive loads. By using an external plastic package, JST30F-1200CW provides a rated insulation voltage of 2000 VRMS, complying with UL standards (File ref: E252906). Package TO-220F is RoHS compliant.



### MAIN FEATURES

| Symbol             | Value    | Unit |
|--------------------|----------|------|
| $I_{T(RMS)}$       | 30       | A    |
| $V_{DRM}/V_{RRM}$  | 1200     | V    |
| $I_{GT\ I/II/III}$ | 35/35/35 | mA   |

### ABSOLUTE MAXIMUM RATINGS

| Parameter                                                                                                        | Symbol       | Value   | Unit                   |
|------------------------------------------------------------------------------------------------------------------|--------------|---------|------------------------|
| Storage junction temperature range                                                                               | $T_{stg}$    | -40-150 | °C                     |
| Operating junction temperature range                                                                             | $T_j$        | -40-125 | °C                     |
| Repetitive peak off-state voltage ( $T_j=25^\circ\text{C}$ )                                                     | $V_{DRM}$    | 1200    | V                      |
| Repetitive peak reverse voltage ( $T_j=25^\circ\text{C}$ )                                                       | $V_{RRM}$    | 1200    | V                      |
| RMS on-state current ( $T_c \leq 71^\circ\text{C}$ )                                                             | $I_{T(RMS)}$ | 30      | A                      |
| Non repetitive surge peak on-state current (full cycle , $t_p=20\text{ms}$ , $T_j=25^\circ\text{C}$ )            | $I_{TSM}$    | 300     | A                      |
| Non repetitive surge peak on-state current (full cycle , $t_p=16.6\text{ms}$ , $T_j=25^\circ\text{C}$ )          |              | 330     |                        |
| $I^2t$ value for fusing ( $t_p=10\text{ms}$ , $T_j=25^\circ\text{C}$ )                                           | $I^2t$       | 450     | $\text{A}^2\text{s}$   |
| Critical rate of rise of on-state current ( $I_G=2 \times I_{GT}$ , $f=100\text{Hz}$ , $T_j=125^\circ\text{C}$ ) | $di/dt$      | 100     | $\text{A}/\mu\text{s}$ |
| Peak gate current ( $t_p=20\mu\text{s}$ , $T_j=125^\circ\text{C}$ )                                              | $I_{GM}$     | 4       | A                      |

|                                                                                      |             |     |    |
|--------------------------------------------------------------------------------------|-------------|-----|----|
| Average gate power dissipation ( $T_j=125^{\circ}\text{C}$ )                         | $P_{G(AV)}$ | 0.5 | W  |
| Peak gate power                                                                      | $P_{GM}$    | 10  | W  |
| Peak pulse voltage<br>( $T_j=25^{\circ}\text{C}$ ; non-repetitive, off-state; FIG.7) | $V_{pp}$    | 2.5 | kV |

**ELECTRICAL CHARACTERISTICS** ( $T_j=25^{\circ}\text{C}$  unless otherwise specified)

| Symbol      | Test Condition                                                                     | Quadrant    | Value |      | Unit             |
|-------------|------------------------------------------------------------------------------------|-------------|-------|------|------------------|
| $I_{GT}$    | $V_D=12\text{V}$ $R_L=33\Omega$                                                    | I - II -III | MAX.  | 35   | mA               |
| $V_{GT}$    |                                                                                    | I - II -III | MAX.  | 1.3  | V                |
| $V_{GD}$    | $V_D=V_{DRM}$ $T_j=125^{\circ}\text{C}$<br>$R_L=3.3\text{k}\Omega$                 | I - II -III | MIN.  | 0.15 | V                |
| $I_L$       | $I_G=1.2I_{GT}$                                                                    | I -III      | MAX.  | 70   | mA               |
|             |                                                                                    | II          |       | 80   |                  |
| $I_H$       | $I_T=500\text{mA}$                                                                 |             | MAX.  | 60   | mA               |
| $dV/dt$     | $V_D=800\text{V}$ Gate Open $T_j=125^{\circ}\text{C}$                              |             | MIN.  | 1000 | V/ $\mu\text{s}$ |
| $(dI/dt)_c$ | $(dV/dt)_c=20\text{V}/\mu\text{s}$ $T_j=125^{\circ}\text{C}$                       |             | MIN.  | 15   | A/ms             |
| $t_{on}$    | $I_G=40\text{mA}$ $I_A=200\text{mA}$ $I_R=20\text{mA}$<br>$T_j=25^{\circ}\text{C}$ |             | TYP.  | 7    | $\mu\text{s}$    |
| $t_{off}$   |                                                                                    |             |       | 50   |                  |


**STATIC CHARACTERISTICS**

| Symbol    | Parameter                                |                           | Value(MAX.) | Unit             |
|-----------|------------------------------------------|---------------------------|-------------|------------------|
| $V_{TM}$  | $I_{TM}=42\text{A}$ $t_p=380\mu\text{s}$ | $T_j=25^{\circ}\text{C}$  | 1.5         | V                |
| $V_{TO}$  | Threshold voltage                        | $T_j=125^{\circ}\text{C}$ | 0.73        | V                |
| $R_D$     | Dynamic resistance                       | $T_j=125^{\circ}\text{C}$ | 25          | $\text{m}\Omega$ |
| $I_{DRM}$ | $V_D=V_{DRM}$ $V_R=V_{RRM}$              | $T_j=25^{\circ}\text{C}$  | 10          | $\mu\text{A}$    |
| $I_{RRM}$ |                                          | $T_j=125^{\circ}\text{C}$ | 4           | mA               |


**THERMAL RESISTANCES**

| Symbol        | Parameter                | Value | Unit                        |
|---------------|--------------------------|-------|-----------------------------|
| $R_{th(j-c)}$ | junction to case (AC)    | 1.3   | $^{\circ}\text{C}/\text{W}$ |
| $R_{th(j-a)}$ | junction to ambient (AC) | 60    | $^{\circ}\text{C}/\text{W}$ |


ORDERING INFORMATION




MARKING




**FIG.1:** Maximum power dissipation versus RMS on-state current




**FIG.3:** Surge peak on-state current versus number of cycles




**FIG.5:** Non-repetitive surge peak on-state current for a sinusoidal pulse with width  $t_p < 20\text{ms}$ , and corresponding value of  $I^2t$  ( $di/dt < 100\text{A}/\mu\text{s}$ )




**FIG.2:** RMS on-state current versus case temperature




**FIG.4:** On-state characteristics



**FIG.6:** Relative variations of gate trigger current, holding current and latching current versus junction temperature



**FIG.7: Test circuit for inductive and resistive loads to IEC-61000-4-5 standards**

## LEAD FORMING AND SOLDERING

Refer to the application note “Assembly Instructions for Thyristors in Through-hole Package” released by JieJie Microelectronics.

**ORDERING INFORMATION**


| Order code    | Voltage<br>V <sub>DRM</sub> /V <sub>RRM</sub> (V) | IGT(mA)      | Package      | Base qty.<br>(pcs) | Delivery<br>mode |
|---------------|---------------------------------------------------|--------------|--------------|--------------------|------------------|
|               |                                                   | I - II - III |              |                    |                  |
| JST30F-1200CW | 1200                                              | 35           | TO-220F(Ins) | 50                 | Tube             |

**Document Revision History**

| Date         | Revision | Changes                        |
|--------------|----------|--------------------------------|
| Apr.11, 2023 | A.1.0    | Last updated                   |
| Oct.13, 2025 | A.1.1    | Revise PACKAGE MECHANICAL DATA |

Technical drawing of a 2-pin plug. The drawing includes a top view, a front view, and a side view. The top view shows a rectangular plug with two pins. The front view shows the plug with dimensions:  $H$  (total height),  $E$  (width),  $I$  (pin width),  $L1$  (pin length),  $L2$  (pin diameter),  $L3$  (plug body length),  $G$  (pin base width),  $M$  (pin base diameter),  $K$  (pin tip length),  $J$  (pin length),  $B$  (pin base diameter), and  $\phi 3.05 \pm 0.25 \text{ mm}$  (pin diameter). The side view shows the plug with dimensions:  $A$  (total height),  $C2$  (plug body height),  $F$  (plug body length),  $D$  (plug body diameter),  $C3$  (pin base length), and  $C$  (pin base diameter). The side view also shows a chamfer angle of  $45^\circ$ .

| Ref. | Dimensions  |      |       |        |       |       |
|------|-------------|------|-------|--------|-------|-------|
|      | Millimeters |      |       | Inches |       |       |
|      | Min.        | Typ. | Max.  | Min.   | Typ.  | Max.  |
| A    | 4.50        |      | 4.90  | 0.177  |       | 0.193 |
| B    | 0.74        | 0.80 | 0.83  | 0.029  | 0.031 | 0.033 |
| C    | 0.47        |      | 0.65  | 0.019  |       | 0.026 |
| C2   | 2.45        |      | 2.75  | 0.096  |       | 0.108 |
| C3   | 2.60        |      | 3.00  | 0.102  |       | 0.118 |
| D    | 8.80        |      | 9.30  | 0.346  |       | 0.366 |
| E    | 9.80        |      | 10.4  | 0.386  |       | 0.410 |
| F    | 6.40        |      | 6.80  | 0.252  |       | 0.268 |
| G    | 2.40        |      | 2.70  | 0.094  |       | 0.106 |
| H    | 28.0        |      | 29.8  | 1.102  |       | 1.173 |
| I    | 4.80        |      | 5.20  | 0.189  |       | 0.205 |
| J    | 12.60       |      | 13.00 | 0.496  |       | 0.512 |
| K    | 9.60        |      | 10.00 | 0.378  |       | 0.394 |
| L1   | 3.20        |      | 3.80  | 0.126  |       | 0.150 |
| L2   | 1.14        |      | 1.70  | 0.045  |       | 0.067 |
| L3   | 3.20        |      | 3.60  | 0.126  |       | 0.142 |
| M    | 4.80        |      | 5.20  | 0.189  |       | 0.205 |
| V1   |             | 45°  |       |        | 45°   |       |



| PACKAGE | OUTLINE | TUBE<br>(PCS) | INNER BOX<br>(PCS) | PER CARTON |
|---------|---------|---------------|--------------------|------------|
| TO-220F | TUBE    | 50            | 1,000              | 5,000      |

Information furnished in this document is believed to be accurate and reliable. However, Jiangsu JieJie Microelectronics Co., Ltd. assumes no responsibility for the consequences of use without consideration for such information nor use beyond it. Information mentioned in this document is subject to change without notice, apart from that when an agreement is signed, Jiangsu JieJie complies with the agreement.

Products and information provided in this document have no infringement of patents. Jiangsu JieJie assumes no responsibility for any infringement of other rights of third parties which may result from the use of such products and information. This document supersedes and replaces all information previously supplied.



is a registered trademark of Jiangsu JieJie Microelectronics Co., Ltd.

Copyright © 2025 Jiangsu JieJie Microelectronics Co., Ltd. All rights reserved.